

FELLER GMBH

A-2525 GUENSELSDORF, AUSTRIA - TEL.: .. 43(2256) 62 32 50 - FAX: .. 43 (2256) 62 32 57
e-mail: sales@feller-at.com <http://www.feller-at.com>

Description: ZA/3-H05VVF3G1,00-C13W/2,50m, grey

(L223)

Rating of cord set: 10A/250Vac

1. PLUG: Type ZA/3

Molded plug according to : SANS 164/1, IS 1293
Rated current and voltage : 16 A, 250 V AC
Plugbase : PA GFR
Construction : double insulation
Pins : brass
Pins outer diameter : grounding O.D. 8,70 mm, part insulated
line and neutral O.D. 7,0 mm
Outer mold : PVC compound, hardness Shore A75-77
Approvals : SABS, CII

2. CORD: Type H05VVF3G1,00mm²

Flexible cord according to : HD 21.5 S3:1994+A1:1999+A2:2001; AS 3191
Marked : *JF*<ÖVE><HAR>H05VVF3G1,0mm2*N1095*CE
*CCC 227 IEC 53(RVV) 300/500 3x1,0*VCTF3CX1,0mm2
Number of cores : 3
Conductor construction : 31x0,195 mm O.D. 1,25mm
Conductor insulation : Extruded PVC O.D. 2,40mm
Jacket : Extruded PVC O.D. 6,80mm +/- 0,20mm
Resistance of conductors : max. 19,5 Ω/km
Dielectric strength : 2kVac, 1min.
Insulation resistance : >0,010MΩ/km
Color of conductors : yellow/green,brown,blue
Approvals : HARMONIZED, ÖVE, CCC, KTL

3. CONNECTOR: Type C13W

Molded connector according to : EN/IEC60320/C13
Rated current and voltage : 10 A, 250 V AC
Construction : double insulation
Contacts of the connection : self-adjusting phosphor bronze CuSn6
Inner insulation : PPO GFR
Outer mold : PVC compound, hardness Shore A 75-77
Approvals : ENEC

Environmental conformity

: EU-Directive 2002/96/EC (WEEE)
EU-Directive 2003/11/EC (Council Directive 76/769/EEC)
EU-Directive 2002/95/EC (RoHS-compliant)


Testing

Electrical testing : 100%
Visual inspection : 100%
High pot test wire to wire : 3.000Vac for 2 sec.
Continuity test : 25Aac to grounding / 20Aac to line and neutral
Polarity test : yes
Skin high pot test : 6.000Vac line to skin

Tolerances not indicated in the drawing: +/- 2 %
design subject to change without prior notice

DATE of ISSUE:	May, 2010		
REV: 3	1	ORIG:	lg

2,50 m



1.

ZAV3

2.

H05VVF3G1,00

3.

C13W

Feller Type: ZAV3 - H05VVF3G1,00 - C13W / 2,50 m, grey

All dimensions in mm

28.05.03



A-2525 Günselsdorf, Austria
Telefon 0043-2256-62325-0
Fax: 0043-2256-62325-7
email: sales@feller-at.com
<http://www.feller-at.com>