

# FELLER GMBH

A-2525 GUENSELSDORF, AUSTRIA - TEL.: .. 43(2256) 62 32 50 - FAX: .. 43 (2256) 62 32 57  
e-mail: sales@feller-at.com <http://www.feller-at.com>

**Description:** SAA/2-H03VVH2F2x0,75-gnet/ 1,70m, black

(L530)

Rating of cord set: 2,5A, 250 Vac

## 1. PLUG: Type SAA/2

Molded plug according to : AS/NZS 3112:2000  
Rated current and voltage : 10A, 250V AC  
Plugbase : PPO GFR  
Pins : solid brass, nickel plated, part insulated, crimped  
Pins dimension : 6,35 mm x 1,63 mm  
Outer mold : PVC compound, hardness Shore A75-77  
Approvals : SAA

## 2. CORD: Type H03VVH2F2X0,75 mm<sup>2</sup>

Flexible cord according to : ÖVE K41a, HD 21.S2; AS3191  
Marked : \*JF\*<ÖVE><HAR>H03VVH2F2X0,75\*N1095\*CE  
Number of cores : 2  
Conductor construction : 23x0,2 mm O.D. 1,10mm  
Conductor insulation : Extruded PVC, O.D. 2,10mm  
Jacket : Extruded PVC, 3,30 mm x 5,40mm +/-0,20mm  
Electrical resistance of conductors : max.26 Ohm/km  
Dielectric strength : 2000 Vac, 1min.  
Insulation resistance : 500Vdc>50Mohms  
Color of conductors : brown, blue  
Approvals : HARMONIZED, VDE, ÖVE, CE BEC, KEMA, S, D, N, FI, SEV, UTE, IMQ, BSI, SAA

## 3. end g net

**Environmental conformity** : EU-Directive 2002/96/EC (WEEE)  
EU-Directive 2003/11/EC (Council Directive 76/769/EEC)  
EU-Directive 2002/95/EC (RoHS-compliant)

## **TESTING**

Electrical testing : 100%  
Visual inspection : 100%  
High pot test wire to wire : 3.000Vac for 2 sec.  
Continuity test : 20Aac to line and neutral  
Skin high pot test : 6.000Vac line to skin

Tolerances not indicated in the drawing: +/- 2 %  
design subject to change without prior notice

DATE of ISSUE:	may, 2011