

CAT. NO. 13VW

FIG. 3

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. 13VW is similar to Cat. No. 13V except it is a right angle cord connector.

1. Cord Entry - Overall dimensions 9/16 in (14.2 mm) tapering to 1/2 in (12.7 mm) by 1/2 in (12.7 mm) by 9/16 in (14.2 mm) long.
- *2. Cord - Listed, Type **SVT, SVTO, SVTOO**, No. 18 AWG; Type **SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO**, No. 18, 17, 16, 14 AWG.
3. Contacts - Nonpolarized, Cat. No. 1307, see Vol. 1C, Sec. 7. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7/8 in (22.2 mm) by 5/8 in (15.8 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-1/4 in (56.1 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component plastic (QMFZ2) Noryl SE1GFN1, flame Class 94HB, manufactured by Sabic Innovative Plastic. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.

CAT. NO. 13VL

ILL. 5

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. 13VL is similar to Cat. No. 13VW except it is a left angle cord connector instead of right angle cord connector.