

CAT. NO. 17V

FIG. 2

(REPRESENTS CAT. NOS. 13V, 13VA AND 13VB)

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. 13V is similar to Cat. No. 17V except it is a 3-wire connector. Refer to Ill. 2 for further details. Cat. Nos. 13VA, 13VB is similar to Cat. No. C13V except they are right angle connector, refer to Ills. 3 and 4 for details.

1. Cord Entry - Overall dimensions 11/16 in (17.4 mm) tapering to 19/32 in (15.1 mm) by 19/32 in (15.1 mm) by 3/4 in (19.0 mm) long.
- \*2. Cord - Listed, **Types SVT, SVTO, SVTOO**, No. 18 AWG; Type **SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO**, No. 18 or 16, 14 AWG.
- \* Alternate - For Cat. Nos. 13V, 13VA, 13VB - Type **SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO**, No. 17 AWG.
3. Contacts - Nonpolarized, Cat. No. 1307, see Vol. 1C, Sec. 7. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7/8 in (22.2 mm) by 5/8 in (15.8 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 3 in (76.2 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component plastic (QMFZ2) Noryl SE1GFN1, flame Class 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.