

CAT. NO. C13
(REPRESENTS CAT. NO. C17)

FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. C17 is similar to Cat. No. C13 except it is a 2-wire connector. Refer to Ill. 1 for further details.

1. Cord Entry - Overall dimensions 9/16 in (14.2 mm) tapering to 15/32 in (11.9 mm) by 9/16 in (14.2 mm) tapering to 15/32 in (11.9 mm) by 3/4 in (19.0 mm) long for Cat. Nos. C13 and C17.

* **2. Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.**

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
	SVT, SVTO, SVTOO	YES	YES
17	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
	SVT, SVTO, SVTOO	YES	YES

3. Contacts - Nonpolarized, Cat. No. 1307, see Vol. 1C, Sec. 7. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 29/32 in (23.0 mm) by 5/8 in (15.8 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-17/32 in (64.2 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component plastic (QMFZ2) Noryl SE1GFN1, flame class 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.