

CAT. NO. C17W  
(REPRESENTS CAT. NOS. C13W)

FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. Nos. C13W and C13WK are similar to Cat. No. C17W except they are a 3-wire connector. Refer to Ills. 1 and 2 for further details.

1. Cord Entry - Overall dimensions 9/16 in (14.2 mm) tapering to 1/2 in (12.7 mm) by 19/32 in (15.1 mm) tapering to 1/2 in (12.7 mm) by 27/32 in (21.4 mm) long.
- \*2. Cord - Flexible cord, Listed (ZJCZ). See the following table for application details.

Cat Nos.	Cord Size (AWG)	Cord Type	USL
C13WK	16	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES
C17W, C13WK	17	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES
C17W, C13WK	18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES

3. Contacts - Nonpolarized, Cat. No. 1307, see Vol. 1C, Sec. 7. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7/8 in (22.2 mm) by 19/32 in (15.1 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 1-11/16 in (42.8 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component plastic (QMFZ2) Noryl SE1GFN1, flame Class 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.