

CAT. NO. C13L

FIG. 2

General - Cat. No. C13L is similar to Cat. No. C13W in Fig. 1 of this report except it is a left angle cord connector.

1. Cord Entry - Overall dimensions 5/8 in (15.8 mm) by 5/8 in (15.8 mm) tapering to 1/2 in (12.7 mm) by 1/2 in (12.7 mm) by 1 in (25.4 mm) long.
- *2. Cord - Flexible cord, Listed (ZJCZ). See the following table for application details.

Cord Size (AWG)	Cord Type	USL
17	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES

3. Contacts - Nonpolarized, Cat. No. 1307, refer to Vol. 1C, Sec. 7 for further details. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7.8 in (22.2 mm) by 19/32 in (15.1 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of this report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-1/32 in (51.6 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component - Plastic (QMFZ2) Noryl SE1GFN1, 94HB flame class, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown) Listee's name or trademark molded on body.