

CAT. NO. C13M

FIG. 6

1. Cord Entry - Overall dimensions approx 9/16 in (14.2 mm) dia by 19/32 in (15.08 mm) long.
- *2. Flexible Cord - Listed, Type **SJT**, **SJTO**, **SJTW**, **SJTOW**, **SJTOOW**, **SJTOO**, No. 18, 17, 16 or 14 AWG.
3. Contacts - Cat. No. 1307, refer to Vol. 1C, Sec. 7 for further details. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7/8 in (22.2 mm) by 19/32 in (15.08 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-5/8 in (66.6 mm) including cord entry.
6. Premold Insert - Molded of Recognized Component - Plastic (QMFZ2) Noryl SE1GFN1, flame class 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 23/32 in (18.2 mm) wide, 1-3/16 in (30.1 mm) long, 7/16 in (11.1 mm) high.
7. Marking - (Not shown). Listee's name or trademark molded on body.