

CAT. NO. C-15

FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. When molded on No. 16 or 14 AWG and rated 250 V, the contacts shall be crimped and soldered to the conductors.

1. Cord Entry - 27/32 in (21.43 mm) long, by 19/32 in (15.08 mm) wide by 11/16 in (17.46 mm) thick tapering to 19/32 in (15.08 mm).
2. Cord - Listed, Type SJT, No. 16 or 14 AWG; Types SVT, SJT, No. 18 AWG.
3. Contacts - Nonpolarized, see Fig. 2 of this report. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - Overall dimensions 7/8 in (22.2 mm) by 19/32 in (15.08 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Thickness of molding material min 3/32 in (2.4 mm) over live parts, overall length 2-3/32 in (53.1 mm) including cord entry but not premold insert.
- \*6. Premold Insert - Molded of Recognized Component (QMFZ2) plastic, PBT, **E202G30**, Flame Class 94V-0 manufactured by **Shinkong**. Overall dimensions 1-3/8 in (34.9 mm) long, 1 in (25.4 mm) wide, 23/32 in (18.25 mm) thick.
7. Marking - (Not shown). Manufacturer's name, trademark or Cat. No. molded on body.