

CAT. NO. C19

FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described.

1. Cord Entry - 25/32 in (19.84 mm) at end of connector. Tapers to 11/16 in (17.46 mm) at cord entrance to connector, 3/4 in (19.05 mm) long.
2. **Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.**

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
14	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
12	ST, STO, STOO, STW, STOW, STOOW	YES	YES

*

3. Contacts - Nonpolarized, see Vol. 1C, Sec. 1. See Section General, Construction, for slot dimensions and polarized wiring if applicable. Contacts recessed min 1/4 in (6.4 mm) from face.
4. Face - 1-3/32 in (27.78 mm) by 25/32 in (19.84 mm).
5. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Min 3/32 in (2.4 mm) over live parts, overall length approx 3-5/32 in (80.16 mm) including cord entry.
6. Enclosure - Molded of Recognized Component (QMFZ2) plastic, Noryl GFN3 manufactured by SABIC Innovative Plastics. Overall dimensions 1-19/32 in (40.48 mm) long, 1-1/32 in (26.19 mm) wide, 11/16 in (17.46 mm) deep, min 1/16 in (1.58 mm) thick.
7. Enclosure - Molded of Recognized Component (QMFZ2) plastic, Noryl SE1GFN1 manufactured by SABIC Innovative Plastics. Two-piece construction, snaps together. Overall dimensions 1-3/8 in (34.9 mm) long, 7/8 in (22.2 mm) wide, 5/8 in (15.87 mm) deep, min 0.045 in (1.14 mm) thick. See ILLs. 1, 1A for details.
8. Pre-Mold - Molded PVC over electrical connections. Overall dimensions 1-1/32 in (26.19 mm) long, 3/4 in (19.05 mm) wide, 17/32 in (13.49 mm) thick.
9. Marking - (Not shown). Manufacturer's name or trademark molded on body.