

CAT. NO. C5

FIG. 1 (M99-07946)

1. Line Contacts - Cat. No. RBB7994.002, refer to Vol. 1C, Sec. 11 for further details.
2. Grounding Contact - Cat. No. 650/03 manufactured by Schatz, refer to Vol. 1C, Sec. 13 for further details.
3. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Min 3/32 in (2.4 mm) thickness of molding material covers live parts, overall dimensions 2-3/16 in (55.5 mm) including cord entry. Reference may be made to Ill. 1 for further details.
4. Face - Overall dimensions approx 11/16 in (17.4 mm) by 1/2 in (12.7 mm).
5. Cord Entry - Overall dimensions 13/32 in (10.3 mm) by 13/32 in (10.3 mm) tapering to 11/32 in (8.7 mm) by 11/32 in (8.7 mm) by 7/16 in (11.1 mm) long.
- *6. Flexible Cord - **Listed Flexible (ZJCZ/7)**. See the following table for details.

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SVT, SVTO, SVTOO	YES	YES

7. Premold - Molded of Recognized Component - Plastic (QMFZ2), Norly SE1GFN1, flame rating 94HB, manufactured by Sabic Innovative Plastics. Overall dimensions 1 in (25.4 mm) long, 5/8 in (15.8 mm) wide, 1/2 in (12.7 mm) high. Reference may be made to Ill. 3 for further details.
8. Marking - (Not shown) Listee's name, trade name or trademark molded on body.