

CAT. NO. C7

FIG. 2 (M75-11699)

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. 70 is similar to that shown in Fig. 1 of this report.

1. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Overall dimensions 1-1/2 in long by 5/8 in wide by 1/4 in thick. Face dimensions 11/32 in wide by 21/32 in long.
2. Contacts - Grothe & Hartmann, Cat. No. 25003-123-111, copper alloy, shaped as shown. Overall dimensions 1/4 in (8 mm) long, 1/8 in (4 mm) dia.
3. Crimp Connections - Copper alloy, formed integrally with contact.
 - A) Lead crimp 1/8 in (4 mm) long by 3/32 in (2.318 mm) wide. B) Insulation crimp 3/32 in (2.318 mm) long by 1/8 (4 mm) wide.
4. Marking - (Not shown). Manufacturer's name or trademark molded on body.
5. **Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.**

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
18	SVT, SVTO, SVTOO	YES	YES
18	SPT-2	YES	YES

*