

CORD CONNECTORS

CAT. NO. C7W (NONPOLARIZED)

FIG. 6 (M98-11656)

General - Cat. No. C7W.

1. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Min 3/32 in (2.4 mm) thickness of molding material covers live parts, overall length 1-7/16 in (36.5 mm).
2. Face - Overall dimensions 5/8 in (15.8 mm) by 5/16 in (7.9 mm). Both ends of face are rounded for Cat. No. C7W. One end of face is rounded, other end is square for Cat. No. C7PW for polarization.
3. Contacts - Cat. No. RBB7994.002, refer to Vol. 1C, Sec. 11 for further details.
4. Cord Entry - Overall dimensions 5/8 in (15.8 mm) long by 3/8 in (9.5 mm) dia.
5. **Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.**

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
18	SVT, SVTO, SVTOO	YES	YES
18	SPT-2	YES	YES

*

6. Pre-mold - Overall dimensions 1-1/32 in (26.2 mm) long, 5/8 in (15.8 mm) wide, 5/16 in (7.9 mm) high.
7. Marking - (Not shown) Listee's name or trademark molded on body.