

ATTACHMENT PLUG
CAT. NO. C14R

FIG. 2 (M90-14997)

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. C14R is similar to Cat. No. 6R except it employs alternate blades.

1. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Overall dimensions 2-9/32 in (57.9 mm) long, 1-13/16 in (46.0 mm) wide including shroud. Shroud min 5/64 in (1.98 mm) thick, 21/32 in (16.6 mm) high from face.
2. Face - Recessed 21/32 in (16.6 mm). Overall dimensions 31/32 in (24.6 mm) by 5/8 in (15.8 mm).
3. Cord Entry - 9/16 in (14.2 mm) by 19/32 in (15.1 mm) by 17/32 in (13.4 mm) long.

4.

Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES	YES
17	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
16	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES
14	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO	YES	YES

*

5. Blades - For No. 18 AWG cord only, folded from approx 0.037 in (0.94 mm) thick copper alloy stock, plating optional, overall length including electrical connections 1-1/32 in (26.2 mm). Refer to Fig. 1 of this report.

Alternate - For No. 18 and 16 AWG cord. Line blade, No. 1409 and grounding blade No. 1408, refer to Vol. 1C, Sec. 6 of this file for details.