**1. PLUG : VIIG**

Molded plug according to	: IEC 60884, CEE (7) VII, KSC8305
Rated current and voltage	: 16A, 250 V AC
Plug base	: Thermoplastic Polyester (PBTP) 30% GF
Construction	: double insulated
Pins	: solid brass, nickel-plated, crimped
Pins outer diameter	: 4,8 mm
Outer mold	: PVC compound, hardness Shore A75-77
Approvals	: VDE, OVE, CEBEC, KEMA, S , D, N, FI, LCIE, IMQ, IMQ, EAC, KTL, SNI
SCIP database	: 60f3e2d1-0a06-4272-8901-d04d26aecd79

2. CORD : H05VVF3G1,50mm2**BLACK**

Flexible cord according to	: OVE K41a, EN 50525, AS3191 : IEC 60227
Marked	*JF*<OVE><HAR>H05VVF3G1,50mm2*N1095*CE*CCC 60227
	IEC 53(RVV) 300/500V 3X1,50mm2*KTL SW01001-2001A*SNI MARK*
	SNI 04-6629.5 Cu/PVC/PVC-f
Number of cores	: 3
Conductor construction	: 29x0,245 mm OD 1,52 mm
Conductor insulation	: Extruded PVC O.D 2,90 mm +/-0,06mm
Jacket	: Extruded PVC O.D 8,20mm +/- 0,20 mm
Température rating	: -20°C up to +70°C
Resistance of conductors	: max. 13,3 Ω/km
Dielectric strength	: 2 kVac, 1min
Insulation resistance	: > 0,010 M Ω/km
Color of conductors	: yellow/green, brown, blue
Approvals	: <HAR>, OVE, KTL, SNI

3. CONNECTOR : C19

Molded connector according to	: EN/IEC 60320/C19? K60320-1
Rated current and voltage	: 16A, 250 V AC
Construction	: double insulation, contact crimped
Contacts of the connection	: self-adjusting phosphor bronze CuSn6
Inner insulation	: PPO GFR
Outer mold	: PVC compound, hardness Shore A 75-77
Approval	: CE, ENEC, KTL, EAC


ENVIRONMENTAL CONFORMITY

EU-Directive 2012/19/EU (WEEE)
 EU-Directive 2011/65/EU
 EU-Directive 1907/2006 EG (REACH compliant)
 High pot test wire to wire : 3kVac for 2 sec
 Continuity test : 20Aac to line and neutral
 Skin high pot test : 6kVac line to skin

TESTING

Electrical testing : 100%
 Visual inspection : 100%
 Polarity test : yes

COMAREL



Feller Type : VIIG - H05VVF3G1,50 - C19 / 2,50m Black

(L716)

All dimensions in mm

ROHS compliant

WWW.COMAREL.FR

136, Rue du 18 Juin – ZA DES METIERS – F-95120 – ERMONT - FRANCE

Tel : +33 1 34 13 72 80 – Mail : info@comarel.fr

SAS AU CAPITAL.DE 50000 EUROS – R.C.S PONTOISE B408 977 643 – SIRET 408 977 643 00027 -APE 4652 Z